


铜版纸157克, 双面印刷, 尺寸335x98mm, 五折六页, 风琴折



User Manual



UC25

Multi-Light Flat Tactical EDC Flashlight

FEATURES

FOUR LIGHT SOURCES

- TN LED Main Light: Up to 3,100 lumens, with a throw distance of 174 meters
- Precision GL Beam: Keeps the target clearly in sight at all times
- UV Light: Identifies authenticity and checks for cleanliness.
- High CRI ≥ 95 Auxiliary Light: Provide true-to-life color rendition and comfortable viewing

INTUITIVE SWITCH DESIGN

- Rotary Magnetic Switch: Cycles through Main Light(White Light) / GL Beam / UV Light / Auxiliary Light
- Side Switch: Turns the flashlight On/Off and adjusts brightness levels
- Tail Tactical Switch: Instant access to Turbo and Strobe modes

CONVENIENT CHARGING

- USB-C Charging Port: Charge anywhere without needing a separate charger
- Battery Level Indicator: Provide clear power status at a glance

TAIL MAGNETIC CAP

- Attach magnetically to most metal surfaces, freeing your hands

PORTABLE & EASY TO CARRY

- Clip: Secures comfortably to a belt or backpack for quick access whenever needed

RUGGED CONSTRUCTION

- Crafted from AL6061-T6 aerospace-grade aluminum with hard-anodized finish
- Rated IP65 for dust and water resistance.
- 1.5m Impact Resistance

FLAT SHAPE & COMPACT SIZE

- Size: 142mm/5.59"(Length) x 31mm/1.22"(Width) x 16mm/0.63"(Height)
- Weight: 137.9g/4.86oz

ACCESSORIES

- 1x UC25 Flashlight; 1x Holster; 1x USB-C Charging Cable;
- 1x User Manual; 1x Warranty Card; 1x Qualification Certificate;
- 1x Warning manual

TECHNICAL PARAMETER

FLI STANDARD	TN 6500K LED										Auxiliary Light			GL Beam		UV	
	Turbo	High	Med2	Med1	Low	Ultra Low	Strobe	High	Med	Low	Ultra Low	High	Low				
3100~700 Lumens	530 Lumens	270 Lumens	130 Lumens	50 Lumens	10 Lumens	3100~700 Lumens	260~80 Lumens	40 Lumens	18 Lumens	3 Lumens	—	—	—				
15s+2h10min	2h35min	6.3h	12h	25h	69h	15s+5h	1min+5h	13h	27h	72h	—	2min+6h	14h				
174m	54m	39m	28m	20m	—	174m	—	—	—	—	—	—	—				
7569cd	729cd	380cd	196cd	100cd	—	7569cd	—	—	—	—	—	—	—				
IP65					✓					1.5 meters							

Notice: The above-mentioned parameters have been measured in accordance with the international flashlight testing standard ANSI/PLATO FL1, and are approximate and may vary from flashlights, batteries, and environments. If you have any questions, please contact customer service.

OPERATIONS

Lock/Unlock

- Lock:** While off, press and hold the side switch 3s to lock. White light flashes 3 times.
- Unlock:** While locked, press and hold the side switch 3s to unlock. White light flashes 3 times.

Light Source Selection

Rotate the magnetic control switch to cycle through modes, Main White Light - GL Beam - UV Light - High CRI Auxiliary Light.

Note: While on, rotating the magnetic switch to change the light source will return it to the memorized mode of the current light source.

Main Light

- On/Off:** Single press side switch.
- Ultra Low:** Press and hold side switch while off.
- Brightness Adjustment:** While on, press and hold side switch to cycle through Low - Med 1 - Med 2 - High (memory function).
- Turbo:** Double press side switch. Double press again to return to memorized setting.
- Strobe:** Triple press side switch.

GL Beam

- On/Off:** Single press side switch.
- Press and hold while off has no function. Press and hold for over 3 seconds to enter lockout mode.

UV Light

- On/Off:** Single press side switch.

Brightness Adjustment: While on, press and hold side switch to adjust between Low - High (memory function). Press and hold while off has no function. Press and hold for over 3 seconds to enter lockout mode.

Auxiliary Light

- On/Off:** Single press side switch.
- Brightness Adjustment:** While on, press and hold side switch to cycle through Low - Med - High (memory function).
- Turbo:** Double press side switch. Press and hold while off has no function. Press and hold for over 3 seconds to enter lockout mode.

Tactical Tail Switch

- Momentary Turbo:** Half press when unlocked.
- Constant Turbo:** Full press to lock Turbo. Half or full press again to return to previous state.
- Strobe:** Double full press.

WARNING

- By using this device, you certify you have read the included User Manual and Warning Card and release the manufacturer and retailers from all liabilities.
- Please use in accordance with applicable laws and regulations.
- Keep out of reach of children.
- DO NOT shine the light directly into human eyes. This may cause temporary blindness, or permanent damage to the eyes.
- DO NOT cover the light head when the flashlight is on, or place the flashlight head on the ground. The radiation energy of the flashlight may cause damage to the flashlight itself, or

- even result in burning to other materials.
- DO NOT modify/disassemble the light, otherwise the user will be in charge of the all responsibilities.
- Please use turbo mode with caution. Turbo greatly reduces the runtime and leads to high temperature on the flashlight surface.
- When the product is used in a low-temperature environment, please try and keep it warm. If the temperature is too cold, it may not reach the highest output.
- If the product is left unused or carrier and transported, please lock the button to avoid accidentally activating the flashlight.
- Please keep the front lens clean. Due to radiation energy, it may heat up foreign matter on the lens which can potentially cause damage.

PRODUCT WARRANTY

- If the customer experiences any problems with an Acebeam product within 15 days of purchase, the dealer will replace that product.
- If an Acebeam flashlight fails during normal use within a period of 2 years of purchase, the dealer will repair or replace the flashlight with the same or similar model.
- The battery comes with a one-year(12 months) warranty from date of purchase. And the warranty does not cover additional accessories.
- The warranty does not cover damage or failure caused by:
 - Rough usage or operation which does not comply with the user manual or product specifications.
 - Unauthorized disassembly, repair or modification. Defects or damaged caused by factors out of Acebeam's control.
 - Battery leakage damaged products.
- If there are any questions about ACEBEAM products, please consider the warranty and contact Acebeam or your original Acebeam dealer for warranty return instructions. Email: cs@acebeam.com

DISCLAIMER CLAUSE

Acebeam is not liable for damages or injuries sustained resulting from the usage of the product inconsistent with the warnings in the manual.



"Follow" us for more information about Acebeam.




ACEBEAM TECHNOLOGY CO., LIMITED
SHENZHEN ZENBON TECHNOLOGY CO., LTD
+86 0755 23036551
www.acebeam.com
cs@acebeam.com
3/F, No.2 Building, Yijiang Industrial Park, Dalang, Longhua, Shenzhen 518100, Guangdong, China

Copyright © 2025 ACEBEAM. All rights reserved.
Powered by Acebeam Technology Co., Ltd



User Manual



UC25

多光源战术EDC手电

产品特性

全能三光源

- TN晶能灯珠主光(白光), 输出可达3100流明, 射程可达174米
- 绿光束精准指示, 让目标时刻清晰
- UV光, 精准鉴别真伪, 检测洁净
- 高显色(CRI≥95)辅光, 真实还原色彩

直观开关设计

- 旋转磁控开关切换主光(白光)/绿光束/UV光/辅光
- 侧按键控制开关手电、档位调节
- 尾部战术开关一键极亮/爆闪

充电便捷

- USB-C充电口, 无需专用充电器
- 电量指示灯, 清晰的电量状态提醒

尾部磁吸设计

- 可磁吸在大多数金属表面, 解放双手, 提高工作效率

便携携带

- 抱夹可固定于腰带或背包, 随时快速取用

坚固结构

- 采用AL6061-T6航空铝合金机身, 军规级硬质氧化
- IP65级防尘防水, 1.5米抗跌落能力

扁平外观 轻量化设计

- 尺寸: 142毫米(长) x 31毫米(宽) x 16毫米(高)
- 重量: 137.9克

包装清单

- 1x UC25手电; 1x 布套; 1x USB-C充电线; 1x 用户手册;
- 1x 保修卡; 1x 合格证; 1x 警告卡

性能参数

FLI STANDARD	TN 6500K LED										辅助灯			UV	
	极亮	高亮	中亮2	中亮1	低亮	极低亮	爆闪	高亮	中亮	低亮	极低亮	绿光束	高亮	低亮	
3100~700 流明	530 流明	270 流明	130 流明	50 流明	10 流明	3100~700 流明	260~80 流明	40 流明	18 流明	3 流明	—	—	—		
15秒+2小时10分钟	2小时35分钟	6.3小时	12小时	25小时	69小时	15秒+5小时	1分钟+5小时	13小时	27小时	72小时	—	2分钟+6小时	14小时		
174米	54米	39米	28米	20米	—	174米	—	—	—	—	—	—	—		
7569坎德拉	729坎德拉	380坎德拉	196坎德拉	100坎德拉	—	7569坎德拉	—	—	—	—	—	—	—		
IP65					✓					1.5米					

注: 以上数据按照国际手电筒测量标准ANSI/PLATO FL1所述之测量方法, 为ACEBEAM实验室实测, 具体使用需要根据实际环境而定, 如有疑问请联系客服。

操作步骤

锁键/解锁

- 锁键:** 关机状态下, 长按三秒锁机, 白光闪烁3下。
- 解锁:** 锁机状态下, 长按三秒解锁, 白光闪烁3下。

选择光源

- 拨动磁控开关可选择光源, 依次为白光(白光) - 绿光束 - UV光 - 高显色辅光。
- 注:** 开机状态下拨动磁控开关切换光源, 会回到当前光源的记忆档位。

主光源模式

- 开/关机:** 单击侧按键。
- 极亮亮:** 关机状态下长按侧按键。
- 档位调节:** 开机状态下, 长按侧按键调档低-中1-中2-高(可记忆)。
- 极亮:** 双击侧按键, 再次双击返回记忆档位。
- 爆闪:** 三击侧按键。

绿光束模式

- 开/关机:** 单击侧按键。
- 关机状态下:** 长按超过3秒进入锁机。

UV光模式

- 开/关机:** 单击侧按键。
- 档位调节:** 开机状态下, 长按侧按键低-高循环(可记忆)。
- 关机状态下:** 长按超过3秒进入锁机。

辅光源模式

- 开/关机:** 单击侧按键。
- 档位调节:** 开机状态下, 长按侧按键低-中-高循环(可记忆)。
- 极亮:** 双击侧按键。
- 关机状态下:** 长按超过3秒进入锁机。

战术尾键

- 瞬时极亮:** 未锁机状态下轻按。
- 锁定极亮:** 重按, 再次轻按或者重按解除锁定回到之前的状态。
- 爆闪:** 双击重按。

警告

- 使用前请先仔细阅读包装内的说明书和警告标签, 并确保已经熟知并遵守。
- 严禁在手电点亮时直接照射眼睛及皮肤, 以免造成视力损伤或皮肤灼伤, 并远离儿童。
- 使用者需按当地法律法规及相关注意事项操作, 出现任何法律问题与制造商及销售商无关。

保养及注意事项

- 请勿自行拆卸部件, 否则将会导致保修失效并可能损坏手电。
- 灯具长时间以极亮档位工作会积累大量的热量并及时导出, 因此手电使用中发热属正常现象。
- 此手电防水效果优良, 但不可作为专业潜水手电使用。

售后/保修条款

- 15天保换: ACEBEAM产品自售出日起15天内, 在正常使用情况下, 如有任何质量问题, 均可向经销商要求免费更换。
- 保修2年: ACEBEAM产品自售出日起2年内, 在正常使用情况下, 如有任何质量问题, 均可享受免费维修服务。
- 电池类产品保修期为1年, 产品附加配件不在保修范围内。
- 本条款不适用于以下情况:
 - 人为破坏, 拆解, 改装本产品;
 - 错误操作导致产品损坏(如电池装反等);
 - 电池漏液导致产品损坏。

- 如对ACEBEAM产品有任何疑问请参照保修条款并联系当地代理商或发邮件到cs@acebeam.com。

免责条款 Acebeam 对因不按照手册中的警告使用产品而造成的损害或伤害不承担任何责任。



深圳市纵邦科技有限公司
+86-755-23036551
www.acebeam.com
cs@acebeam.com
深圳市龙华新区大浪街道华韵路300号仪佳场工业园2栋3楼
Copyright © 2025 ACEBEAM
深圳市纵邦科技有限公司有对本说明书内容的最终解释权 and 修改权